

TECHNICAL DATA SHEET

PRODUCT SPECIFICATION		
Width		190mm
Length		2200mm
Pack Size		2.508m ² (up to 4 shorter planks per pack)
Planks per Pack		6 Planks
Pack Weight		24.45kg
Total Thickness		14mm nominal
Surface Coating		UV Cured Acrylic Lacquer
Surface Treatment		Brushed Matt Finish

PHYSICAL PROPERTY	TEST METHOD	SUPREME OAK
Construction		3 layers
Top Layer		2.5mm nominal
Colours in Range		10 designs
Edge Detail		Micro-Bevel 4 sides
Grading	Internal (Vibrant)	Unlimited knots ≤ 80mm (EN1310)
Colour Variation		Moderate to High
Installation Method		Floating or glue down
Joining System		Uniclic® 4 sides
Moisture Content		6% - 8% MC
Slip Resistance	AS 4586:2013	P3
Abrasion Group	DIN 68861	>550
Fire Resistance	ASISO 9239.1-2003	4.6 Kw/m2 Smoke 13%
Thermal Resistance		R = 0.147
Electric Behavior		Static free
Indoor Air Quality - VOC	EN 717.1	=.02mg/m ³ (<0.124mg/m ³) E1 (large chamber)
Warranty	Domestic Use	20-year wear and lifetime structural*
	Commercial Use	Available upon request*

***Warranty Details**

Supreme Oak Flooring Warranty Terms and Conditions are available from Carpet Call Australia Pty Ltd or from an authorised Supreme Oak Retailer.