
MAINTENANCE GUIDE

Regular cleaning and maintenance of your new PVC floors will keep them looking beautiful and prolong the products service life.

Up keeping your floor

TIMBERTRENDS LVT has various colours and pattern choices and a number of advantages such as outstanding durability and comfortable viewpoint of walk. It also has these features of easy application and maintenance, but regular cleaning and up-keeping is required to maintain the product correctly..



1. Daily Cleaning (Residential, Commercial)

- 1) Dirt left on the floor can damage and tarnish the surface of the floor. So, please make sure to remove these immediately and clean on a regular basis.
- 2) Use Universal cleaning solution as instructed on the bottle to clean the PVC floor.
- 3) When the mop is too wet, the binding part or edge of the floor tiles can expand or widen creating a gap due to moisture. We recommend the use of a really well rung mop. (Do not apply too much water to this floor)
- 4) When there is a solvent material, paint, copy liquid or any other chemicals spilt on the surface, you should remove it with alcohol immediately. In case of using a strong solvent such as thinner or acetone, the contamination gets worse and it causes discoloration.
- 5) Contamination by oils and fats should be cleaned with a neutral detergent.

2. Surface protection treatment (Commercial product)

- 1) The surface protection treatment for maintenance is not necessarily required, however it is recommended to be applied on a regular basis when the coating layer on the surface is used in high traffic area's with long-term use. This is in order to prevent further contamination. (see your retailer for the recommended suitable products that can be used)
- 2) When processing surface protection treatment, you need to clean the dirt adhering to surface using a neutral detergent first, and apply a thin wax 2~3 times. Then, you will see a clean surface without any stain.
- 3) Surface protection treatment varies depending on the operating conditions, but the treatment in the following table is recommended in general for commercial use.

Walk type	Wet rag	Period of treatment	REMARK
Heavy walk	Frequently	2~3 times/week	Department store, office, public office
Medium walk		2~3 times/month	Exhibition, general office
Light walk		once/6 months	Residential(living room, kitchen, study)

- 4) Please select the appropriate products for surface protection(wax) according to use of the floor(Glossy, Matt, wood, PVC).

3. Other considerations(Residential,, Commercial)

- 1) Installation of mats at the entrance of the building is recommended to prevent inflow of sand and dust adhering to shoes. (do not use rubber backed mats)
- 2) It is necessary to block the sunlight with curtains as discoloration and shrinkage can occur if exposed to direct sunlight.
- 3) PVC floors can be tarnished by rubber mounted under furniture, sofa and home appliances, so please use it with protective materials (tin foil paper) so that it does not directly touch the PVC floor.
- 4) When moving heavy furniture such as pianos, it must be moved with care so that the floor is not pushed back or stabbed by sharp edges.
- 5) It is necessary to prevent defects due to moisture with silicon finish between the wall and threshold near kitchen sink and toilet doorway.